



The X-Tinguish® X-Treme is used by Firefighters, Police, Armed forces and First Responders as a highly effective suppression tool against early stage and fully developed fires. The X-Tinguish® X-Treme is non-pressurized and is deployed manually by pulling a pin which will set off an electronic ignition system.

After triggering the X-Tinguish® X-Treme, an aerosol mist is generated, which expands volumetrically, flooding the space and suppressing the flames within seconds. The X-Tinguish® X-Treme is designed for the use on class A, B, C and K fires. In an enclosure up to 5,300Cu.Ft.

WHEN SECONDS COUNT!
“PULL THE PIN AND THROW IT IN!”



FIRE SUPPRESSION TECHNOLOGY

- does not remove oxygen
- does not utilize super cooling gases
- is not harmful to people or animals
- is not harmful to the atmosphere
- Zero ODP and Zero GWP
- does not increase pressure
- Non-toxic, non-conductive, non-corrosive
- Ignition method: Manual pull-pin, electronic

Flame Guard USA
1000 Butterfield Rd.
Suite 1029
Vernon Hills, IL 60061 USA
Ph: (011) 815-219-4074
Fax: (011) 847-387-3824
URL: <https://www.flameguardusa.com>
Email: sales@flameguardusa.com



The World's Most Advanced Aerosol Firefighting Tool!

- COVERAGE UP TO 5,300 CU.FT.
- EMITS NO FLAME!
- NO PYROTECHNIC IGNITER!
- WATER RESISTANT SHELL
- ELECTRIC START!
- RUGGED STEEL BODY CONSTRUCTION
- OPERATES TO -65°F
- FULLY WARRANTIED
- DEPLOYS AFTER 8 SECOND DELAY
- THE SAFEST AEROSOL FIREFIGHTING TOOL AVAILABLE TODAY!!



MAIN FEATURES

The X-Tinguish® X-Treme

- Offers extraordinary knock down as well as fast suppression capabilities
- Reduces temperatures by as much as 1,000°F in 30 seconds
- Can cut water usage by as much as 80%, when used properly
- Is SNAP listed by the US EPA
- Is environmentally friendly (ODP 0%, GWP 0%)
- Does not reduce or deplete (O²) oxygen
- Can eliminate flashover and backdraft
- Is Non-Toxic, Non-Corrosive, Non-Conductive
- Highly Efficient and Suitable against A-B-C-K class fires
- **IS NOT** pressurized!
- Has a 5-year battery life
- Has a 15-year shelf life
- Includes a new "R-pin" that protects igniter pin from being accidentally removed.
- LED light turns red when the unit is activated!



SPECIFICATIONS

Total weight	13.90Lbs. / 6.3 kg.
Compound weight	6.40 Lbs. / 2.9 kg.
Volume coverage (up to)	≤ 5,300cu.ft. / 150 m ³
Discharge time	33 seconds
Activation method	Manual pull pin
Operational to	-65°F / -55°C below zero

