

FG 1300 FIRE SUPPRESSION ACTIVATION PANEL WITH WEB ENABLED CONTROLLER



7.71 x 7.71 x 5.90 in. / 195.83 x 195.83 x
149.86 mm. / 3.35 lbs. / IP66 of IEC 529 and
NEMA 1, 2, 4, and 4X specifications



The Components utilized in this system meet the highest International standards and testing.



1000 Butterfield Rd. • Suite 1029 • Vernon Hills, IL • 60061

Phone: (855) 377-2100 • (815) 219-4074

www.flameguardusa.com • info@flameguardusa.com

Innovation in Fire Suppression Since 2012

X-Tinguish® is a Registered Trademark of Flame Guard USA, LLC, I-FIRE is a Trademark of Flame Guard USA, LLC. All Rights Reserved.





I-Fire™ Aerosol Fire Suppression System Activation Panels



FG 1100

FG 1200

FG 1300

	FG 1100	FG 1200	FG 1300
Battery only or AC with power supply fire panel	✓	✓	✓
Aerosol Release capable: up to 4 generators	✓	✓	✓
Optical/smoke detectors an/or linear heat detection cable	✓	✓	✓
IP66 of IEC 529 and NEMA 1, 2, 4, and 4X specifications	✓	✓	✓
Voltage Free Contacts	✓	✓	✓
Programmable time delay function from 10-30 sec.	✓	✓	✓
Logging, Storage: Nonvolatile Flash			✓
UL 61010-1 Compliance			✓
Wireless access point			✓
Built-in web server			✓
Wireless WI-FI 802.11 B/G/N			
WI-FI enabled relay			✓
Web enabled programmable controller			✓
Power over Ethernet (PoE)			✓
Email Alerting			✓
HTTP, HTTPS, SSL, XML, Modbus TCP/IP, SNMP, SMTP, Remote Services			✓
24 V Power Supply			✓
105dB siren and strobe		✓	✓
Control, monitor, and log up to 100 inputs and/or outputs from up to 32 remote I/O modules			✓